

NEW FROM SOLAX

# X1-HYBRID G4



## X1-Hybrid G4

3.0kW/3.7kW/4.6kW/  
5.0kW/6.0kW/7.5kW

## Features

### High-efficient

- 200% PV oversized and up to 110% AC overload output
- Higher efficiency on charging and discharging, up to 97.0%
- Built-in shadow tracking function

### Economic

- 16A DC input current, support high power solar panel
- Up to 150% PV input
- Store the surplus energy from PV to battery
- Low start output voltage makes inverter longer working time
- Less energy loss on battery to inverter

### Intelligent

- Up to 120% EPS output for 1h
- Switchover time <10ms
- Quick configuration with U-disk
- Lithium-ion & Lead-acid battery compatible
- CT compatible, loads respond within 0.3s
- Intelligent loads management (e.g., Heat pump)
- On & Off-grid parallel function, up to 15kW
- 5 work modes, 2 charging periods available
- VPP ready, ancillary service in power market

### Safe

- IP65 protection level
- Integrated SPD

### For More Informations Contact Us

[www.solaxpower.com](http://www.solaxpower.com)  
AU: +61 1300 476529  
DE: +49 6142 4091664

Global: +86 571-56260008  
UK: +44 2476 586998  
NL: +31 (0) 852 737932

[info@solaxpower.com](mailto:info@solaxpower.com)  
[service@solaxpower.com](mailto:service@solaxpower.com)





# X1-HYBRID G4 (SINGLE-PHASE)

X1-HYBRID-3.0-D X1-HYBRID-3.7-D X1-HYBRID-4.6-D X1-HYBRID-5.0-D X1-HYBRID-6.0-D X1-HYBRID-7.5-D  
 X1-HYBRID-3.0-M X1-HYBRID-3.7-M X1-HYBRID-4.6-M X1-HYBRID-5.0-M X1-HYBRID-6.0-M X1-HYBRID-7.5-M

## DC INPUT

Max. PV array power [Wp]	6000	7400	9200	10000	12000	15000
Max. PV input power <sup>①</sup> (PV1+PV2) [Wp]	4500	5500	6900	7500	9000	10000
Max. PV input voltage [V]	600	600	600	600	600	600
Start output voltage [V]	90	90	90	90	90	90
Nominal input voltage [V]	360	360	360	360	360	360
MPPT voltage range [V]	70 ~ 550	70 ~ 550	70 ~ 550	70 ~ 550	70 ~ 550	70 ~ 550
No. of MPPT trackers / Strings per MPP tracker	2 (1/1)	2 (1/1)	2 (1/1)	2 (1/1)	2 (1/1)	2 (1/1)
Max. input current (input PV1 / input PV 2) [A]	16 / 16	16 / 16	16 / 16	16 / 16	16 / 16	16 / 16
Max. short circuit current (input PV1 / input PV 2) [A]	20 / 20	20 / 20	20 / 20	20 / 20	20 / 20	20 / 20

## AC INPUT & OUTPUT

Nominal AC output power [W]	3000	3680	4600	5000 <small>(Germany 4600, AU 4999)</small>	6000	7500
Max. AC output apparent power [VA]	3300	3680	4999 <small>(Germany 4600)</small>	5500 (4600 for VDE4105, 4999 for AS4777)	6600	7500
Max. AC output current [A]	14.4	16	21.7 <small>(Germany 20)</small>	23.9 <small>(Germany 20, AU 21.7)</small>	28.6	32.6
Max. AC input apparent power [VA]	6300	7360	9200	9200	9200	9200
Max. AC input current [A]	27.4	32	40	40	40	40
Nominal AC voltage [V]	230 / 240					
Nominal grid frequency [Hz]	50 / 60					
Displacement power factor	0.8 leading ~ 0.8 lagging					
THDi (rated power) [%]	<2					

## BATTERY DATA

Battery type	Lithium-ion battery / Lead-acid Battery					
Battery voltage range [V]	80 ~ 480					
Max. continuous charge / discharge current [A]	30					

## EPS (OFF-GRID OR BACK-UP) OUTPUT (WITH BATTERY)

Nominal output power [W]	3000	3680	4600	5000	6000	7500
Peak apparent power [VA]	3600, 1h	4416, 1h	5520, 1h	6000, 1h	7200, 10min	7500
Max. continuous current [A]	13	16	21.7	21.7	26.1	32.6
Nominal voltage [V]; Frequency [Hz]	230; 50 / 60					
Switch time [ms]	<10					
Parallel operation	YES					

## SYSTEM DATA

Max. efficiency [%]	97.6					
Euro. efficiency [%]	97.0					
Battery charge / discharge efficiency [%] <sup>②</sup>	97.0 / 97.0					
Degree of protection	IP65					
Operating temperature range [°C]	-35 ~ +60 (Derating above +45)					
Max. operation altitude [m]	<3000					
Relative humidity [%]	0 ~ 100					
Typical noise emission [dB]	<30					
Storage temperature [°C]	-40 ~ +65					
Dimensions (WxHxD) [mm]	482x417x181					
Net weight [kg]	24					
Cooling concept	Nature cooling					
Communication interfaces	CT/Meter (optional), External control RS485, Pocket WiFi (Optional: Pocket Lan/4G), DRM, USB Upgrade, NTC (optional)					

## POWER CONSUMPTION

Internal consumption (night) [W]	<17W for standby, <2.7W for idle					
----------------------------------	----------------------------------	--	--	--	--	--

## STANDARD

Safety	EN/IEC62109-1/-2					
EMC	EN61000-6-1/2/3/4; EN61000-3-2/3/11/12					
Certification	VDE4105, G99, G98, AS4777, EN50549, CEI 0-21, IEC61727, RD1699, NRS 097-2-1, PEA/MEA, VFR2019, C10/11					

①: Indicates that all model single PV1 & PV2 input power upper limit is 5000 W. ["Max. PV input power<sup>①</sup> (PV1+PV2)" restriction takes precedence].

②: PV to BAT Max. efficiency 97.0%, BAT to AC Max. efficiency 97.0%.